



Guelph Permeameter Supplied Complete with Extension Kit.

Code: [25-0650](#)

Product Group: [Guelph Permeameter](#), [Guelph Permeameter](#)

- Lightweight and portable
- Robust construction
- Requires only 2.5 litres of water
- Results usually within 2 hours

The Guelph Permeameter is used to obtain accurate measurements of hydraulic conductivity, soil sorptivity and soil matrix flux potential. These three factors govern how liquids will move through an unsaturated soil profile.

Recent significant advances in both the theoretical and practical techniques of measuring soil hydraulic conductivity have been made by the University of Guelph, Canada. This has resulted in the development of the Guelph Permeameter, utilising the Constant Head Well principle.

Standards

ASTM D5126

Further Information

Guelph Permeameter Set Includes:-

- 1 Field Tripod
- 1 Well Auger
- 1 Well Tripod
- 1 Preparation Tool
- 1 Hand Pump
- 1 Extension Kit (extends depth by 800 mm)
- 1 Collapsible Water Container
- 1 Set of Instructions and Carrying Case

Specification

Cell	Plated seamless tube 100 mm diameter x 130 mm height
Capacity	3.18 Litres
Base	Porous plate with three tie rods
Top plate	Machined to accept smaller tubes
Net Weight	13.6 kg
Overall Weight	111 kg
Permeameter	High impact polycarbonate, molded elastomers.

Product Sheet

www.ele.com
+44 (0) 01525 249 200



Auger	2" (50.8 mm) diam.; machined steel.
Carrying Case	Die-cut foam for parts storage.
Test Time	1/2 – 2 hours.
Test Depth	15 to 75 cm (0.5 to 2.5 ft).
Hydraulic Conductivity Range	10-4 to 10-8 m/sec (10-2 to 10-6 cm/sec).
Weight	Net 30 lbs. (13 .6 kg).

Accessories



Permeameter Extension Kit

Code: [25-0655](#)