



Unconfined Compression Tester, Hand-Operated

Code: 25-3605

Product Group: Unconfined Compression Tester,
Hand-Operated

6.6 kN load capacity.

Standards

ASTM D2166, AASHTO T208

Specification

| | |
|------------------|--|
| Specimen Height | Up to 8" (203 mm). |
| Platens | 3" (76 mm) diam.; with concentric grooves for centering specimen. |
| Proving Ring | Plated steel; complete with dial indicator and calibration charts in English and Metric units. |
| Strain Indicator | English: 1.0" range x 0.001" graduations. Metric: 25 mm range x 0.01 mm graduations. |
| Hand Crank | Two-piece; aluminum. |
| Base | One-piece; cast aluminum. |
| Crosshead | High-strength aluminum. |
| Dimensions | 10-5/8" w. x 6-3/8" d. x 26-1/4" h. (270 x 162 x 667 mm). |
| Weight | Net 43 lbs. (19.5 kg); Shpg. 58 lbs. (26.3 kg). |

Accessories



Unconfined Compression Test Accessory Set, English

Code: 25-3997



Unconfined Compression Test Accessory Set, Metric

Code: 25-3998

Alternatives



Unconfined Compression Tester, Hand-Operated

Code: 25-3602



Unconfined Compression Tester, Hand-Operated

Code: 25-3604



Versa-Loader

Code: [25-3525/02](#)