



Los Angeles Abrasion Machine with CE Safety Cabinet W/ Microswitches. 220-240V 60Hz 1Ph.

Code: 42-5310/06

Product Group: [Los Angeles Abrasion Machine](#)

The machine consists of a closed hollow cylindrical steel drum rotating around its horizontal axis on ball bearing units mounted on a sturdy base framework. Also the full enclosure ensures noise is minimized.

The drum is driven at a speed of between 30 - 33 rpm via an enclosed belt drive arrangement from an electric motor/gearbox unit situated on the base frame. Inside the drum a full length steel shelf is attached, accessed by a dust-proof opening.

The cylinder incorporates a removable internal shelf, one shelf position is provided to meet the requirements of both the ASTM and EN test standards.

Controls are located easily on the right-hand side of the machine at convenient operator height.

Start and stop push buttons and a subtracting revolution counter allows the user to preset the number of revolutions before an automatic stop.

Further Information

NOT AVAILABLE FOR SALE IN THE USA

Specification

| | |
|--------------|--|
| Description | Los Angeles Abrasion Machine with CE Safety Cabinet 220 - 240 V 60Hz |
| Power Supply | 220 - 240 V AC, 60 Hz, 1 ph |
| EN 1097-2 | Yes |
| ASTM C131 | Yes |
| ASTM C535 | Yes |
| NF P18-573 | Yes |

Accessories

Set of 12 Abrasive Charges (ASTM).

Code: [42-5300/10](#)



Set of 12 Abrasive Charges EN)

Code: [42-5305/10](#)



Alternatives



Los Angeles Abrasion Machine Meets ASTM and European Standards. 220-240V 50Hz 1Ph.

Code: [42-5315/01](#)



Los Angeles Abrasion Machine Meets ASTM and European Standards. 220-240V 60Hz 1Ph.

Code: [42-5315/06](#)