



Pocket Shearmeter with 3 Vanes 0 to 1Kgf/Cm2 X 0.5Kgf/Cm2.

Code: [26-2261](#)

Product Group: [Torvane Shear Device, Pocket Shearmeter](#)

The shearmeter can be used on tube samples, on the sides of pits, cuttings etc. It is an invaluable tool for initial site investigation work.

Further Information

Complete with sensitive vane, standard vane and high-capacity vane. Range 0 to 1 x 0.05 kgf/cm².

Specification

Vane Driver	1.6" (41 mm) diam. x 3.2" (81 mm) l. with vane attached.
Dial Scale	1 kg/sq. cm (tons/sq. ft.) x 0.05 subdivisions.
Carrying Case	Plastic; 6" w. x 4" d. x 2" h. (152 x 102 x 51 mm).
Weight	Net 10.5 oz. (300 g).

Accessories



Laboratory Vane Apparatus with 4 Springs and 12.7mm Vane; Hand Operated.

Code: [26-2270](#)

Spares/Consumables



High-Capacity Vane

Code: [26-2261/14](#)



Laboratory Vane Apparatus (Motorised)

Code: [26-2275/01](#)



Sensitive Vane

Code: [26-2261/10](#)



Standard Vane

Code: [26-2261/12](#)

Alternatives



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 110-120V 50/60Hz 1Ph.

Code: [26-2114/02](#)



Digital Direct/Residual Shear Apparatus Complete with Lever Loading Assembly. 220-240V 50/60Hz 1Ph.

Code: [26-2114/01](#)



Hand Vane Tester

Code: 26-3346